

ZORA 110-110 Voice Patch Cord

ZORA 110-110 Voice Patch Cord for structured cabling systems; carries digital, voice signals and is suitable for Category 3 applications.



ZORA 100-110 Voice Patch Cord Features

- 1、 Adopting multi-strand conductor structure, the jumper wire is soft, easy to bend and not easy to break;
- 2、 Duckbill termination at both ends to ensure excellent performance.

Reference Standard

- ISO/IEC 11801

Technical Specifications

Cable Construction	
Conductor	
Material	Stranded Anneal Copper Wire
Wire Size	24AWG
Insulation	
Material	PE
Thickness	Nom. 0.18mm

Diameter	0.97mm
Jacket	
Material	PVC or LSZH optional
Thickness	0.50mm
Diameter	3.00±0.2mm
Jacket Colors	Available in multiple colors and customizable
Flame rating	CM Style
Maximum tensile strength	1 kgf/mm2

Duckbill Plug	
Housing	PC
Contact Material	Copper alloy 50u" gold plated over nickel
Strength	20lbs. min
Durability	750 cycles min.

Electrical	
Impedance	93.8Ω ± 15 Ω
Capacitance unbalance pair to ground	max. 330pf/100m Max
D.C.R (Max.)	Rated value 14.8 ohm/100m at 20°C
DC Insulation Resistance	500MΩ/100m min.
Dielectric Strength	AC-500V/1 Min