

## ZORA 24-port Cat 5e Unshielded Modular Patch Panel

ZORA 24-port Cat 5e unshielded modular patch panels are used for data network communications, patch cord-connected wiring devices, main wiring closets and distribution closets.



### ZORA 24-port Cat 5e Unshielded Modular Patch Panel Features

- 1、 Made of cold rolled steel plate, with plastic spraying surface treatment, beautiful and generous;
- 2、 Modularized design, suitable for quick installation of modules;
- 3、 Piano key type cable management bracket, for bundling cable management, effectively reduce cable tension;
- 4、 Front intuitive grouping labeling, to the network management, maintenance provides convenience;
- 5、 It can be directly installed in 19" standard cabinet, wall-mounted cabinet, etc..

### Reference Standard

- ANSI/TIA 568.2-D
- ISO/IEC 11801

## Technical Specifications

| Construction  |                                                                                                                     |
|---------------|---------------------------------------------------------------------------------------------------------------------|
| Body          |                                                                                                                     |
| Body Material | Adoption of high-quality SPCC cold-rolled steel plate                                                               |
| Body Surface  | The surface has undergone special spray coating treatment, which is sturdy, beautiful, and not easily scratched     |
| Front         |                                                                                                                     |
| Front Label   | Positive and intuitive grouped labeling area provides easy management of written labels                             |
| Rear          |                                                                                                                     |
| Rear Tray     | Straight cable management bracket on the back for bundling and cable management, effectively reducing cable tension |

| Physical Ranges       |                                                                       |
|-----------------------|-----------------------------------------------------------------------|
| Operating Temperature | -20°C ~ +70°C to meet the requirements of 48 hours of salt spray test |
| Norm                  | Standard 19" rack mount, height: 1U                                   |
| Mounting              | Modular design for quick installation of ZORA modules                 |