

ZORA Network Cabinet

ZORA network cabinets are used to install 19-inch rack-mounted hardware and storage of IT equipment required by the customer (such as switches, routers, communications equipment and other lightweight equipment) floor to wall cabinets, can support hanging walls, can also be placed on the floor, with good network cable and communications cable management management of management capabilities.



ZORA network cabinet Features

- 1、 19-inch standard cabinet construction design;
- 2、 Transparent tempered glass front door, hexagonal mesh door strips, single-opening steel rear door, maximum opening up to 180°;
- 3、 Front and rear welded frame assembly cabinet, static load capacity up to 1000kg;
- 4、 Front and rear knockout holes in the top and bottom plates are designed to feed the wires flexibly;
- 5、 Top panel mounts the fan unit from top to bottom for easy installation and enhanced cooling capacity;
- 6、 Quick release side panels on both sides of the cabinet for easy disassembly and installation;

Reference Standard

- GB/T 19520.16-2015
- ANSI/EIA RS-310-D
- IEC60297-2

Technical specification

Structure	
Main part	
Makings	Made of high quality SPCC cold rolled steel plate
Surface	Degreased, pickled, phosphated, electrostatically sprayed
Color	Black
Front door	
Makings	Tempered glass door with single opening mesh, long handle lock, max. 180° opening
Back door	
Makings	Single opening steel plate door, small round lock, maximum opening 180°
Side Panel	

makings	Quick-open side steel plate with plastic clasp and pre-drilled hole for small round lock mounting
Internal composition	
Frame	Front and rear welded frame, reserved holes for cable management and parallel cabinet
Angle Gauge	4 mounting angle gauges, bi-directional silkscreen U number
Side Mounting Beam	Fingerprint, corrosion and heat resistance, 135° folded edges for high strength
Top Plate	Front and rear knock-down hole alignment design, with fan unit cooling function, reserved cover mounting holes
Base Plate	Front and rear knock-down hole alignment design, middle removable metal cover, reserved cover mounting holes
Tray	Standard tray for cabinets, load capacity of 110kg
Fan	2-position/4-position fan unit, 220V AC fan 8-position 10A new national standard 5-hole power distribution unit 20/40 sets M6 plum groove screws, card screw accessories, 1 plum groove wrench M12 Top-to-bottom mounting, 220V AC fan
PDU	8-position 10A new national standard 5-hole power distribution unit
Kit	20/40 sets of M6 plum groove screws, jam nut fittings, 1 plum groove wrench
Casters, Feet	M12 adjustable feet, 2" universal heavy-duty casters

Physical property								
Static load	1000KG							
Protection rating	IP20							
Cabinet width (mm)	600							
Cabinet depth (mm)	600							
Cabinet height (mm)	933	1111	1200	1333	1555	1778	2000	2222
U Position	18	22	24	27	32	37	42	47

