

ZORA Voice Module

The ZORA Voice Module is used for voice communication, in conjunction with a message socket panel or desktop box in the workspace.



ZORA Voice Module Features

- 1、Shell material: polycarbonate engineering plastics, impact resistance, flame retardant PC material, strong resistance to damage;
- 2、To ensure that the card connection is more stable, the number of times to play the line \geq 200 times;
- 3、Socket gold pin gold-plated to ensure excellent contact performance;
- 4、Free of wire type module, to ensure reliable termination performance requirements.

Reference Standard

- ANSI/TIA 568 C.2
- ISO/IEC 11801

Technical Specifications

| Construction | |
|-------------------|--------------------------------------|
| Body | |
| Connector Housing | High-impact, Flame Retardant Plastic |
| Standard | UL94V-0 rated |
| Front Connection | |
| Contact Type | Spring Wire |
| Material | Phosphor Bronze Alloy |
| Contact Plating | Nickel then gold plated |
| Rear Terminals | |
| Terminal Type | No-punch line |

| Physical Ranges | |
|-------------------------------|---|
| Temperature Range | Storage : -40 to +70°C Operational : -10 to +60°C |
| Relative Humidity | Operational : Max. non-condensing 93% |
| Retention | 50N (11 lbs) for 60s ± 5s |
| Insertion/Extraction Life | ≥750 |
| Insertion/Extraction Strength | ≥800grams |

| Electrical | |
|--|--------------|
| Minimum insulation resistance | 100 mΩ |
| Dielectric strength (core-to-core, 1 min DC) | 1kV |
| Flexible wire contact resistance | 20 mΩ max. |
| Rated voltage/current | 150VAC/0.75A |